TECHNICAL DATASHEET / OUTDOOR

X-1000



PRODUCT SPECIFICATION		
Pixel pitch (mm)	2.9	3.9
Model code	XS-O-P290	XS-O-P390
DISPLAY PERFORMANCE		
Standard brightness (nits)	4,500	
Optional brightness (nits)	Up to 5,000	
Pixel density (px/m²)	112,896	65,536
Cabinet resolution (px)	168 × 336	128 × 256
Module resolution (px)	168 × 84	128 × 64
Scan mode	1/21	1/16
Refresh rate (Hz)	3,840 / 7,680 by configuration	
Grayscale / contrast ratio	16 bit / 5,000:1	
Viewing angle (H / V)	145° / 145°	
MECHANICAL & SERVICE		
Cabinet size (W × H × D, mm)	500 × 1000 × 84	
Cabinet net weight	14.4 kg / 31.75 lb	
Module size (W × H, mm)	500 × 250	
Cabinet material	Die-cast aluminum	
Service access	Front	
ELECTRICAL & CONTROL		
Input voltage	100-240 V AC	
Control system	Novastar	
Power consumption	Specified with brightness configuration	
ENVIRONMENT & WARRANTY		
IP rating (front / rear)	IP65 / IP54	
Operating temperature	-20 to +60 °C	
Operating humidity	10%-90%	
Warranty	3 years	

Specify the brightness, refresh rate and receiving-card configuration with your quotation. Confirm the electrical schedule before sizing power distribution.

doitvision.com/product/x-1000-series/